

**HYMER**



# SECURE ACCESS TO THE RECYCLING CENTRE

Can be moved by one person, slip-resistant in wet conditions and built for maximum stability – access technology for the requirements of modern recycling centres.

# MOBILE STAIRS WITH PLATFORM

- With double-sided handrails on the stair and all-round platform railings.
- Ergonomic and coated for clean hands.
- All castors braked.
- Mobile cross-beams in signal colour for good visibility.
- Robust support construction allows high heights without losing stability.
- Shipping in preassembled assemblies.

## Features:

- Railing height 1,100 mm.
- **Permissible load steps 150 kg.**
- **Total permissible load 300 kg.**

[hymer-configurator.com](http://hymer-configurator.com)



## QUICKLY AND EASILY CONFIGURABLE OPTIONS:



Step width optionally 600, 800 or 1,000 mm



Stair angles from 35°–75° in 5° increments



Standing heights in 10 mm increments



Platform lengths in 50 mm increments



Fixed or removable stair and platform railings



Various step and platform treads from R11 to R13



Chassis optionally with swivel or fixed castors



Optionally with electrical battery brake system

# MOBILE STOCKER'S LADDER R13, SINGLE-SIDED ACCESSIBLE


- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Spacious work surface and three-sided guardrail for safe, ergonomic work.
- Non-slip, convenient ascent thanks to the large step.
- Effortless manoeuvring thanks to innovative, swivelling spring-loaded castors. Spring force individually adjustable for different load ranges.
- Magnetic front plate with holes (Ø 8.5 mm) for fastening attachments using hooks or magnets.
- Shipped in pre-assembled modules for quick and easy installation.

## Features:

- Step depth 200 mm (aluminium perforated steps).
- Platform dimensions 600 x 800 mm.
- Guardrail height 1,050 mm.



638805

EN  
131-7Max.  
150 kg10  
YEAR  
GUARANTEE★ ★ ★  
MADE IN  
GERMANY

Number of steps incl. platform	3	4	5	6	7	8
Stile (approx. mm)	80	80	80	80	80	80
Standing height (height to platform) (approx. m)	0.73	0.95	1.20	1.45	1.70	1.95
Reach height (approx. m)	2.73	2.95	3.20	3.45	3.70	3.95
Vertical height (approx. m)	1.78	2.00	2.25	2.50	2.75	3.00
Width (approx. mm)	773	831	897	963	1,028	1,094
Distance from front to wall (approx. mm)	87	126	170	215	259	303
Base width (approx. m)	1.27	1.44	1.63	1.82	2.01	2.20
Weight (approx. kg)	38.1	42.2	46.4	51.3	56.2	61.0
Order no.	638803	638804	638805	638806	638807	638808

Note: We advise the use of handrails on both sides from size 5 upwards.

## Recommended accessories:



**Self-closing gate**  
Order no. 0055811



**Handrail**  
Order no. 0055769 for number of steps 4+5  
Order no. 0055768 for number of steps 6+7  
Order no. 0055751 for number of steps 8



**Toeboard set**  
Order no. 0055807

# Hymer-Leichtmetallbau GmbH & Co. KG

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

international-sales@hymer-alu.de | [hymer-access.com](https://hymer-access.com)

## hymer-access.com

You can also download all  
brochures from our website:

