



**H  
Y  
M  
E  
R**

# **HIGHER WITH SAFETY**

Our new products for safe  
and efficient work.



---

# TABLE OF CONTENTS

## LADDERS AND STEPS

- 04 Aluminium step
- 05 Step extension ladder, two-section
- 06 Hookable extension ladder
- 07 Step ladder with platform, single-sided accessible
- 08 Step ladder, double-sided accessible
- 09 Rung ladder, double-sided accessible
- 10 Rung leaning ladder
- 11 Platform ladder HYMER PROTECT C
- 12 Platform ladder with long handrail
- 13 Machine step R13

## ACCESSORIES

- 14 Railing lateral for aluminium step, usable on both sides
- 14 Railing frontal for aluminium step
- 14 Handrail for aluminium step, usable on both sides
- 14 Curved cross-beam for step extension ladder, two-section
- 14 Protection-KIT for roof ladders

# ALUMINIUM STEP

- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Non-slip, convenient ascent thanks to the large step.
- Shipped fully pre-assembled at the factory.

## Features:

- Step depth 200 mm (aluminium profile steps).
- Step width optionally 600 or 800 mm.
- Platform depth 400 mm.
- Permissible load steps 150 kg.
- Permissible load platform 300 kg.

EN  
14183

**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY



68810805

Step width (mm)	600			800			
Number of steps incl. platform	2	3	4	2	3	4	5
Standing height (height of platform) (approx. m)	0.40	0.60	0.80	0.40	0.60	0.80	1.00
Reach height (approx. m)	2.40	2.60	2.80	2.40	2.60	2.80	3.00
Width (approx. mm)	689	716	743	889	916	943	969
Overhang (approx. m)	0.75	0.95	1.15	0.75	0.95	1.15	1.35
Weight (approx. kg)	8.5	12.7	16.9	9.5	14.3	19.0	23.8
Order no.	68810602	68810603	68810604	68810802	68810803	68810804	68810805

## Recommended accessories:



Railing lateral  
Page 14



Railing frontal  
Page 14



Handrail, usable  
on both sides  
Page 14



# STEP EXTENSION LADDER, TWO-SECTION

- Ergonomic working on 80 mm step depth on the upper section. Front step edges flush with stile.
- Lower weight due to the combination of steps and rungs.
- Increased slip resistance of steps and rungs thanks to a high rib extruded profile.
- Easier extension and retraction of the ladder thanks to steel guide fittings with plastic sliders.

**Features:**

- Ladder inner width 300 mm (top section).
- Solid steel fittings.
- Press-fitted ladder feet.



EN  
131

**R11**

Max.  
150 kg

**10**  
YEAR  
GUARANTEE

MADE IN  
GERMANY

Number of rungs/steps	2×8	2×10	2×12	2×14
Stile top/bottom (approx. mm)	83/66	83/66	83/71	83/83
Number of rungs/steps at max. extension	14	17	21	25
Length retracted (approx. m)	2.33	2.89	3.45	4.01
Length extended (approx. m)	4.01	4.85	5.97	7.09
Standing height (approx. m)	2.78	3.56	4.60	5.64
Reach height (approx. m)	4.78	5.56	6.60	7.64
Width extended top/bottom (approx. mm)	355/750	355/948	355/948	355/1,200
Weight (approx. kg)	11.2	13.7	16.7	19.3
Order no.	484616	484620	484624	484628



You don't want to compromise on work safety, but need more flexibility when using the ladder?  
Use the curved cross-beam for increased ground clearance and more adaptability:  
Order no. 0055628 for size 2×8+2×10  
Order no. 0055629 for size 2×12  
Order no. 0055630 for size 2×14  
See also page 14.



# HOOKABLE EXTENSION LADDER

- Non-slip, ribbed, rolled profile rungs.
- Robust guide fittings made of steel.
- Secure attachment of the ladder thanks to preassembled, stable suspension hooks.
- Space-saving storage when retracted.
- The variable angle of inclination allows some height compensation.

## Features:

- Ladder inner width 300 mm (top section).
- Press-fitted ladder feet.
- Angle of inclination between 65° and 75°.
- Hook size 30 mm.

Max.  
150 kg



**10**

YEAR  
GUARANTEE



MADE IN  
GERMANY



494620

Number of rungs	2x7	2x8	2x10
Stile top/bottom (approx. mm)	60/60	60/60	66/66
Number of rungs at max. extension	12	14	17
Length retracted (approx. m)	2.14	2.42	2.98
Length extended (approx. m)	3.54	4.10	4.94
Standing height (approx. m)	1.00 - 2.35	1.27 - 2.89	1.81 - 3.70
Reach height (approx. m)	3.00 - 4.35	3.27 - 4.89	3.81 - 5.70
Vertical height up to leaning point (approx. m)	2.04 - 3.38	2.31 - 3.92	3.12 - 4.73
Width extended top/bottom (approx. mm)	355/424	355/424	355/424
Weight (approx. kg)	7.8	8.2	10.8
Order no.	494614	494626	494620

Note: This ladder is not a leaning ladder as stipulated by EN 131-1 and may only be used when hooked in place.

# STEP LADDER WITH PLATFORM, SINGLE-SIDED ACCESSIBLE


EN  
131

Max.  
150 kg  
↓  
[ ]

- Ergonomic working on 88 mm step depth.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

**Features:**

- Platform dimensions 250 x 250 mm.
- Approved for 1,000 V.
- Legal warranty.



Number of steps incl. platform	4	5	6
Stile (approx. mm)	58	58	58
Length (approx. m)	1.66	1.91	2.16
Standing height (height to platform) (approx. m)	0.94	1.17	1.41
Reach height (approx. m)	2.94	3.17	3.41
Vertical height (approx. m)	1.56	1.79	2.03
Width top/bottom (approx. mm)	310/470	310/500	310/530
Base width (approx. m)	0.80	0.97	1.14
Weight (approx. kg)	7.9	9.4	11.4
Order no.	392604	392605	392606

# STEP LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

Max.  
150 kg  
↓  
[ ]

- Ergonomic working on 88 mm step depth.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- High-strength perlon straps provide reliable safety strut.

**Features:**

- **Approved for 1,000 V.**
- **Legal warranty.**



Number of steps	2x3	2x4	2x5
Stile (approx. mm)	58	58	58
Length (approx. m)	0.75	1.00	1.25
Standing height (approx. m)	0.25	0.48	0.72
Reach height (approx. m)	2.25	2.48	2.72
Vertical height (approx. m)	0.70	0.94	1.17
Width top/bottom (approx. mm)	350/450	350/470	350/500
Base width (approx. m)	0.63	0.80	0.97
Weight (approx. kg)	5.6	7.6	9.4
Order no.	392406	392408	392410



# RUNG LADDER, DOUBLE-SIDED ACCESSIBLE

EN  
131

Max.  
150 kg  
↓  
[ ]

- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.
- Equipped with comfort rungs from the third to the sixth rung from above.
- High-strength perlon straps provide reliable safety strut.

**Features:**

- **Comfort rung depth of 52 mm.**
- **Approved for 1,000 V.**
- **Legal warranty.**



Number of rungs	2x6	2x7	2x8
Stile (approx. mm)	58	58	58
Length (approx. m)	1.83	2.11	2.39
Standing height (approx. m)	1.03	1.30	1.56
Reach height (approx. m)	3.03	3.30	3.56
Vertical height (approx. m)	1.71	1.98	2.24
Width top/bottom (approx. mm)	350/540	350/580	350/610
Base width (approx. m)	1.33	1.52	1.71
Weight (approx. kg)	10.1	11.6	13.2
Order no.	392312	392314	392316

# RUNG LEANING LADDER

- Non-slip, ribbed rungs.
- 100% metal-free. All components made of (glass fibre) plastic.
- Particularly suitable for the chemical, electrical and food industries.

**Features:**

- **Approved for 1,000 V.**
- **Legal warranty.**

EN  
131

Max.  
150 kg  
↓  
[ ]



Number of rungs	6	8	10
Stile (approx. mm)	58	58	58
Length (approx. m)	1.93	2.49	3.05
Standing height (approx. m)	0.81	1.35	1.89
Reach height (approx. m)	2.81	3.35	3.89
Width top/bottom (approx. mm)	410/410	410/410	410/810
Weight (approx. kg)	4.5	6.2	7.4
Ladder bottom	A	A	B
Order no.	391106	391108	391110

# PLATFORM LADDER

## HYMER **PROTECT C**

- Hands-free, safe working thanks to fall protection on all sides.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Comfortable way up thanks to 80 mm step depth.
- Highly stable thanks to foldable, transport-optimised stabilisers.
- Optimum transport by means of tip and roll wheels.
- Brace-free support section for more flexible usage.

### Features:

- Platform dimensions 500 x 424 mm.



EN  
131-7

NF P 93-  
352/353



Max.  
150 kg

**10**  
YEAR  
GUARANTEE




Number of steps incl. platform	2	3	4	5	6
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	1.61	1.86	2.11	2.36	2.61
Standing height (height to platform) (approx. m)	0.46	0.69	0.92	1.16	1.39
Reach height (approx. m)	2.46	2.69	2.92	3.16	3.39
Vertical height (approx. m)	1.51	1.74	1.97	2.21	2.44
Width (approx. mm)	572	1,168	1,168	1,730	1,730
Base width (approx. m)	0.81	1.04	1.20	1.36	1.51
Folded LxWxH (approx. m)	1.75x0.58x0.28	2.00x0.61x0.32	2.26x0.61x0.32	2.51x0.61x0.32	2.76x0.61x0.32
Weight (approx. kg)	11.1	15.3	15.8	18.2	19.3
Foldable stabilisers	-	✓	✓	✓	✓
Order no.	838302	838303	838304	838305	838306

# PLATFORM LADDER WITH LONG HANDRAIL

- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Ergonomic working on 80 mm step depth. Front step edges flush with stile.
- Detachable, rigid brace prevents accidental folding.
- Ergonomically shaped handrails on both sides.
- Conical design ensures ladder stability.

## Features:

- Platform dimensions 440 x 400 mm.
- Guardrail height above platform 1,000 mm.



EN  
131



Max.  
150 kg  
↓

**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY

Number of steps incl. platform	4	5	6	8	10
Stile (approx. mm)	71	71	71	71	71
Length (approx. m)	2.10	2.35	2.60	3.10	3.60
Standing height (height to platform) (approx. m)	0.95	1.18	1.42	1.88	2.34
Reach height (approx. m)	2.95	3.18	3.42	3.88	4.34
Vertical height (approx. m)	1.97	2.20	2.43	2.89	3.36
Width (approx. mm)	653	677	700	747	793
Base width (approx. m)	0.99	1.15	1.30	1.62	1.94
Weight (approx. kg)	10.3	11.5	12.5	15.7	19.0
Order no.	807804	807805	807806	807808	807810

# MACHINE STEP R13

- Work safety in the highest slip resistance class R13. Suitable for use in oily areas.
- Comfortable and safe standing for longer periods of work thanks to the large platform.
- Non-slip, convenient ascent thanks to the large step.
- Extremely high stability for heavy-duty use.
- Lightweight for ergonomic positioning.

## Features:

- Aluminium perforated plate R13.
- Platform dimensions 580 x 350 mm.

EN  
14183



Max.  
150 kg  
↓  
[Platform]

**10**  
YEAR  
GUARANTEE

★ ★ ★  
MADE IN  
GERMANY



Number of steps incl. platform	1	2	3	4	5
Standing height (approx. m)	0.20	0.40	0.60	0.80	1.00
Reach height (approx. m)	2.20	2.40	2.60	2.80	3.00
Overhang (approx. m)	0.38	0.63	0.87	1.10	1.34
Width (approx. mm)	600	680	700	730	760
Weight (approx. kg)	2.8	5.6	7.9	10.4	14.6
Order no.	6878164	6878264	6878364	6878464	6878564





## Railing lateral for aluminium step, usable on both sides

- Can be mounted on the right, left or both sides.
- Self assembly by using tools.
- Including fastening material.

For type	6881	
For number of steps	2-5	
Weight (approx. kg)	6.5	
Order no.	0055633	



## Railing frontal for aluminium step

- Can only be used in combination with two lateral railings (0055633).
- Self assembly by using tools.
- Including fastening material.

For type	6881	
For step width (mm)	600	800
Weight (approx. kg)	1.6	2.1
Order no.	0055635	0055634



## Handrail for aluminium step, usable on both sides

- Can only be used in combination with the lateral railing (0055633).
- Note: Handrail only possible from size 4!
- Self assembly by using tools.
- Including fastening material.

For type	6881	
For number of steps	4+5	
Weight (approx. kg)	8.5	
Order no.	0055632	



## Curved cross-beam for step extension ladder, two-section

- For increased ground clearance and more adaptability.
- Self assembly by using tools.
- Including fastening material.

For type	4846		
For number of rungs/steps	2x8+2x10	2x12	2x14
Length (approx. mm)	876	1,056	1,075
Weight (approx. kg)	1.2	1.4	1.4
Order no.	0055628	0055629	0055630



## Protection-KIT for roof ladders

- To protect the roofing and ladder.
- Content: 2 adhesive strips.

For type	4092+4093+4095+4096	
Dim. LxWxH (approx. mm)	1,950x20x3	
Material	rubber (EPDM)	
Weight (approx. kg)	0.2	
Order no.	0055610	



# **Hymer-Leichtmetallbau GmbH & Co. KG**

Käferhofen 10 | 88239 Wangen | Germany

Telephone +49 75 22 700-700

international-sales@hymer-alu.de | [hymer-access.com](https://hymer-access.com)

## **hymer-access.com**

You can also download all  
brochures from our website:



Written information on the products and images thereof may differ from the actual design in individual cases.  
Errors, price changes and design modifications are also reserved.

Version: 05/2024